



...Your promise, our packaging

Compose your own ideal FIBC

1. Weight

Between 500 and 2500 kg

2. Bag type

4 loop, Q-bag

3. Extra

Filling- and/or discharging spout

4. Height

Depending on bottom size and volume. (Ideal would be a filling height of max. 2 x the bottom size)

5. Type

Uncoated, coated or with liner

Standard height of a pallet is 15 cm.
Necessary height to load/unload a container is 10 cm at the top and bottom.

To compose your own ideal FIBC you need the following information:

Safe Working Load	:	kg
Safety Factor	:	
Material	:	uncoated / coated PP fabric, gr/m ₂
Inner size	:	cm
Seams	:	standard / dust proof
Top	:	
Bottom	:	
Coating	:	
Liner	:	
Print	:	
Loops	:	4 lifting loops of cm, cross corner
Document holder	:	

20' container	Max. load
Width: 2.35 m.	10/22 pallets (80 x 120)
Length: 5.89 m.	10/20 pallets (100 x 120)
Height: 2.39 m.	10/20 pallets (115 x 115)
	150 bales

40' container	Max. load
Width: 2.35 m.	22/44 pallets (80 x 120)
Length: 12.05 m.	20/40 pallets (100 x 120)
Height: 2.39 m.	20/40 pallets (115 x 115)
	300 bales





FIBC specifications

...Your promise, our packaging

SF = Safety Factor FIBC's

- 5:1 – Single Use
- 6:1 – Standard Duty
- 8:1 – Heavy Duty

SWL-Safe Working Load

- | | |
|-----------|-----------|
| 500 kg. | 1.250 kg. |
| 600 kg. | 1.500 kg. |
| 750 kg. | 2.000 kg. |
| 1.000 kg. | 2.500 kg. |

Extra

- Anti static
- Conductive
- Printed with company logo
- Dangerous goods
- Food stuff

Volume	Bottom size 75 x 75 cm.	Bottom size 90 x 90 cm.	Bottom size 96 x 96 mm.	Bottom size 108 x 108 cm.
M3	Height in cm.	Height in cm.	Height in cm.	Height in cm.
0,3				
0,4				
0,5				
0,6	107	74		
0,7	125	86		
0,8	143	98	87	
0,9	160	111	98	
1.0	178	125	108	91
1.1		136	120	100
1,2		148	130	109
1,3		160	141	118
1,4		173	152	127
1,5		185	163	136
1,6		197	174	145
1,7			185	154
1,8			196	163
1,9				172
2,0				181
2,1				190
2,2				199

Type

O	uncoated, without liner
G	coated PP
OL	uncoated with PE liner
C	conductive

Available FIBC types

HBO	4-loop bag with open top
HBS	4 loop bags with skirt
HBC / QHBC	4-loop bag with filling spout
HBOC	4-loop bag with open top and discharging spout
HBSC / QHBSC	4-loop bag with skirt and discharging spout
HBCC / QHBCC	4-loop bag with filling and discharging spout

Sizes filling and discharging spouts

Diameter:	Ø 35 cm.	Length	50 cm.
Diameter:	Ø 45 cm.	Length	60 cm.
Diameter:	Ø 50 cm.	Length	100 cm.

More information?

Exim BV/ Zakkencentrale BV

Cairostraat 50
3047 BC Rotterdam
The Netherlands

- ☎ ++31(0)10 4370055
- ☎ ++31(0)10 4624630
- ✉ info@zakkencentrale.nl

EXIM article code: 1.000 – HB – C – C – 90 x 90 x 120 G

1000	HB	C	C	90 x 90 x 120	G
Weight	Bag type	filling	Spout discharging	Spout sizes	Coated